

Dustproof



Waterproof



# IP56/68 Rating

高防护風扇系列

尺寸 (mm)	机型	IP56	IP68	额定电压 (VDC)	轴承 ⊙ 2 BALL	转速 (RPM)	风量 (CFM)	风压 (Inch-H2O)	噪音 (db(A))	重量 (g)
40x40x28	GF40282BX-1000C		SEP、QEP	24	⊙	17600	24.6	2.07	58.1	46.0
	GF40282B1-1000C		SEP、QEP	24	⊙	14600	20.4	1.41	54.0	46.0
	GF40282B2-1000C		SEP、QEP	24	⊙	13100	18.3	1.13	51.7	46.0
	GF40282B3-1000C		SEP、QEP	24	⊙	10500	14.7	0.73	46.8	46.0
60x60x15	GF60151B6-1E00C	AC9	AE9	12	⊙	4500	21.3	0.18	34.5	47.0
	GF60151B7-1E00C	AC9	AE9	12	⊙	3900	18.2	0.13	29.8	47.0
	GF60151B8-1E00C	AC9	AE9	12	⊙	3200	14.5	0.09	24.9	47.0
	GF60151B9-1E00C	AC9	AE9	12	⊙	2300	10.6	0.05	17.1	47.0
Ø84.9X15.4	GF60151B9-1E01C	AC9	AE9	12	⊙	2200	9.8	0.05	17.1	45.0
60x60x25	GF60252BX-1000C		SEP、QEP	24	⊙	12900	54.8	1.44	55.4	84.0
	GF60252B1-1000C		SEP、QEP	24	⊙	11500	48.8	1.23	52.7	84.0
	GF60252B2-1000C		SEP、QEP	24	⊙	9000	38.3	0.75	48.9	84.0
	GF60252B3-1000C		SEP、QEP	24	⊙	6450	27.4	0.38	41.7	84.0
80x80x25	GF80251B1-000C	AC9	AE9	12	⊙	4800	60.0	0.41	47.5	105.0
	GF80251B2-000C	AC9	AE9	12	⊙	4500	57.0	0.35	46.0	105.0
	GF80251B3-000C	AC9	AE9	12	⊙	4200	53.0	0.30	44.5	105.0
	GF80251B5-000C	AC9	AE9	12	⊙	3200	41.0	0.18	33.0	87.0
	GF80251B6-000C	AC9	AE9	12	⊙	2900	37.0	0.15	30.0	87.0
	GF80251B7-000C	AC9	AE9	12	⊙	2600	33.0	0.11	28.0	87.0
	GE80252B1-000C	AC9	AE9	24	⊙	4800	60.0	0.41	47.5	105.0
	GE80252B2-000C	AC9	AE9	24	⊙	4500	57.0	0.35	46.0	105.0
	GE80252B3-000C	AC9	AE9	24	⊙	4200	53.0	0.30	44.5	105.0
	GF80252B5-000C	AC9	AE9	24	⊙	3200	41.0	0.18	33.0	87.0
	GF80252B6-000C	AC9	AE9	24	⊙	2900	37.0	0.15	30.0	87.0
	GF80252B7-000C	AC9	AE9	24	⊙	2600	33.0	0.11	28.0	87.0
80x80x32	GF80321B1-000C	AC9	AE9	12	⊙	4800	59.4	0.36	45.2	109.0
	GF80321B2-000C	AC9	AE9	12	⊙	4500	55.9	0.32	43.1	109.0
	GF80321B3-000C	AC9	AE9	12	⊙	4100	50.3	0.27	41.1	109.0
80x80x38	GF80382BX-1000C		SEP、QEP	24	⊙	10000	133.0	1.76	64.3	235.0
	GF80382B1-1000C		SEP、QEP	24	⊙	8000	107.3	1.14	59.6	235.0
92x92x25	GF92251B1-000C	AC9	AE9	12	⊙	4500	75.0	0.35	47.0	113.0
	GF92251B2-000C	AC9	AE9	12	⊙	4200	70.0	0.30	45.0	113.0
	GF92251B3-000C	AC9	AE9	12	⊙	3900	65.0	0.25	43.0	113.0
	GF92251B5-000C	AC9	AE9	12	⊙	3000	51.5	0.15	34.0	99.0
	GF92251B6-000C	AC9	AE9	12	⊙	2700	45.0	0.13	32.0	99.0
	GF92251B7-000C	AC9	AE9	12	⊙	2400	39.5	0.10	28.0	99.0
	GE92252B1-000C	AC9	AE9	24	⊙	4500	75.0	0.35	47.0	113.0
	GE92252B2-000C	AC9	AE9	24	⊙	4200	70.0	0.30	45.0	113.0
	GE92252B3-000C	AC9	AE9	24	⊙	3900	65.0	0.25	43.0	113.0
	GF92252B5-000C	AC9	AE9	24	⊙	3000	51.5	0.15	34.0	99.0
	GF92252B6-000C	AC9	AE9	24	⊙	2700	45.0	0.13	32.0	99.0
	GF92252B7-000C	AC9	AE9	24	⊙	2400	39.5	0.10	28.0	99.0
92x92x38	GF92382BX-1000C		SEP、QEP	24	⊙	9000	172.9	1.73	66.8	260.0
	GF92382B1-1000C		SEP、QEP	24	⊙	7200	145.3	1.20	60.6	260.0

电话：13790667800※

如有特殊规格需求，请与Sunon业务人员联络

※ 此产品目录之规格仅供参考。WWW.SUNON-MAGLEV.COM

# Meets GR487

符合GR487盐雾测试标准，盐雾环境条件下适用

环境测试：符合GR-487-CORE(2000), Section3.34.1 Salt Fog Test Procedure.



尺寸 (mm)	机型	额定电压 (VDC)	轴承 ☉ 2 BALL	转速 (RPM)	风量 (CFM)	风压 (Inch-H <sub>2</sub> O)	噪音 (db(A))	重量 (g)
40x40x28	GF40282BX-1000C-SDP	24	☉	17600	24.6	2.07	58.1	46.0
	GF40282B1-1000C-SDP	24	☉	14600	20.4	1.41	54.0	46.0
	GF40282B2-1000C-SDP	24	☉	13100	18.3	1.13	51.7	46.0
	GF40282B3-1000C-SDP	24	☉	10500	14.7	0.73	46.8	46.0
	GF40282BX-1000C-QDP	24	☉	17600	24.6	2.07	58.1	46.0
	GF40282B1-1000C-QDP	24	☉	14600	20.4	1.41	54.0	46.0
	GF40282B2-1000C-QDP	24	☉	13100	18.3	1.13	51.7	46.0
	GF40282B3-1000C-QDP	24	☉	10500	14.7	0.73	46.8	46.0
60x60x25	GF60252BX-1000C-SDP	24	☉	12900	54.8	1.44	55.4	84.0
	GF60252B1-1000C-SDP	24	☉	11500	48.8	1.23	52.7	84.0
	GF60252B2-1000C-SDP	24	☉	9000	38.3	0.75	48.9	84.0
	GF60252B3-1000C-SDP	24	☉	6450	27.4	0.38	41.7	84.0
	GF60252BX-1000C-QDP	24	☉	12900	54.8	1.44	55.4	84.0
	GF60252B1-1000C-QDP	24	☉	11500	48.8	1.23	52.7	84.0
	GF60252B2-1000C-QDP	24	☉	9000	38.3	0.75	48.9	84.0
	GF60252B3-1000C-QDP	24	☉	6450	27.4	0.38	41.7	84.0
80x80x25	GF80251B5-000C-AD9	12	☉	3200	41.0	0.18	33.0	87.0
	GF80251B6-000C-AD9	12	☉	2900	37.0	0.15	30.0	87.0
	GF80251B7-000C-AD9	12	☉	2600	33.0	0.11	28.0	87.0
	GF80252B5-000C-AD9	24	☉	3200	41.0	0.18	33.0	87.0
	GF80252B6-000C-AD9	24	☉	2900	37.0	0.15	30.0	87.0
	GF80252B7-000C-AD9	24	☉	2600	33.0	0.11	28.0	87.0
80x80x38	GF80382BX-1000C-SDP	24	☉	10000	133	1.76	64.3	235.0
	GF80382B1-1000C-SDP	24	☉	8000	107.3	1.14	59.6	235.0
	GF80382BX-1000C-QDP	24	☉	10000	133	1.76	64.3	235.0
	GF80382B1-1000C-QDP	24	☉	8000	107.3	1.14	59.6	235.0
92x92x25	GF92251B5-000C-AD9	12	☉	3000	51.5	0.15	34.0	99.0
	GF92251B6-000C-AD9	12	☉	2700	45.0	0.13	32.0	99.0
	GF92251B7-000C-AD9	12	☉	2400	39.5	0.10	28.0	99.0
	GF92252B5-000C-AD9	24	☉	3000	51.5	0.15	34.0	99.0
	GF92252B6-000C-AD9	24	☉	2700	45.0	0.13	32.0	99.0
	GF92252B7-000C-AD9	24	☉	2400	39.5	0.10	28.0	99.0
92x92x38	GF92382BX-1000C-SDP	24	☉	9000	172.9	1.73	66.8	260.0
	GF92382B1-1000C-SDP	24	☉	7200	145.3	1.2	60.6	260.0
	GF92382BX-1000C-QDP	24	☉	9000	172.9	1.73	66.8	260.0
	GF92382B1-1000C-QDP	24	☉	7200	145.3	1.2	60.6	260.0